


# BATTERY SAFE OPERATION GUIDELINES

Autel Smart Controller SE



## Disclaimer

Autel Smart Controller SE is powered by a lithium-ion battery. Please ensure that all the following guidelines are strictly followed. No responsibility is assumed by us for any consequence resulting from any wrong or improper use of operation, etc. of the product.

## Operation Guidelines

### Charge

- Never out of the max charge current as mentioned in specification.
- Never out of the max charge voltage as mentioned in specification.
- Please refer to the temperature range as specification.

### Discharge Current

The discharge current is not allowed to out of max current as specification. Otherwise, the battery will be over heat and capacity fading.

### Discharge Temperature

Please refer to the temperature range as specification.

### Over-discharge

It's workable if over charge and discharge for a short while but not allow to do it for a long time. Over discharge may result in disappear self-energy. Please keep a certain electric quantity to prevent over discharge.

## Storage

- Store the battery in cool, dry and well-ventilated conditions.
- Please store the battery in the adequate temperature as mentioned in specification. When battery is delivered, if the capacity is about 60%. Suggest to recharge it after more than 6 months. When battery is charged full, Suggest to recharge it after more than 9 months.
- Regulations vary for different countries. Dispose of in accordance with local regulations.

## Other Chemical Reaction

- The battery performance will reduce if over time using or unused for a long time due to It's a reaction of chemical. In addition, the battery life will be shorten or injury or damage itself from electrolyte leakage, heating ignition or explosion for improper handling. It's necessary to replace battery if unable to charge for a long time even with proper way.

## Warnings

- Do not make the battery exposure or thrown into fire.
- Never reverse charge the battery.
- Never short circuit the battery.
- Avoid excessive physical shock or vibration.
- Do not disassemble or deform the battery.
- Never allow the battery to get wet or be immersed in water.
- Do not use different types of battery together.
- Keep away from children.
- Charge at the appropriate conditions.
- Never use the faulty charger to charging.
- Never keep charging more than 24 hours.

## Specification

Model	PT803254-2S
Rated Capacity	1900 mAh
Nominal Voltage	7.7 Vdc
Max Charging Voltage	8.8 Vdc
Max Charging Current	2 A
Charging Temperature	5 ~ 45°C (41 ~ 113°F)
Max Discharging Current	2 A
Discharge Temperature	-20 ~ 60°C (-4 ~ 140°F)
Storage Temperature	>3months: -20°C~25°C (-4°F~77°F) 1~3 months: -20°C~45°C(-4°F~113°F) <1month: -20°C~60°C(-4°F~140°F)

Autel Robotics Co., Ltd.  
18th Floor, Block C1, Nanshan iPark, No. 1001 Xueyuan Avenue,  
Nanshan District, Shenzhen, Guangdong, 518055, China  
22522 29th Dr SE STE 101, Bothell, WA 98021 United States  
Toll-free: (844) MY AUTEL or (844) 692-8835  
[www.autelrobotics.com](http://www.autelrobotics.com)